

# Full Electric Stacker

## Triplex mast 4.5m with free lifting

- Capacity 1500kg.
- Lifting height 4500mm.
- Full free lifting height 1550mm.
- Heavy duty design with top quality mast construction.
- Powerful drive wheel and power unit made in Europe.
- Top quality electronic control system from Curtis.
- Conforms to EN 1757-1:2001, EN1727.

Model	FK1545	BK1545
Type	Standard	Platform
Capacity (kg)	1500	
Load Centre (C) (mm)	600	
Max. Fork Height (h3) (mm)	4500	
Lowered Fork Height (h) (mm)	90	
Full Free Lifting Height (h4) (mm)	1550	
Fork Length (l) (mm)	1150	
Fork Overall Width (M) (mm)	560	
Fork Individual Width (N) (mm)	160	
Travelling Speed (with & without load) (km/h)	5.2/6.8	
Lifting Speed (with & without load) (mm/s)	127/170	
Lowering Speed (with & without load) (mm/s)	150/128	
Motors	Travelling (W/V)	1200/24
	Lifting (W/V)	3000/24
Front Roller, Tandem (mm)	Ø78 x 70	
Rear Roller (mm)	Ø150 x 50	
Drive Wheel (mm)	Ø250 x 80	
Traction Battery	240Ah/24V	
Battery Charger	30A/24V	
Weight of Battery (kg)	230	
Turning Radius (Wa) (mm)	1605	2065
Overall Dimensions (mm)	2013x1080x2175	2507x1080x2175
Net Weight (without battery) (kg)	1010	1035
Minimum Qty. (pcs)	2	

Weight of the battery: 230 kg.



FK1545



BK1545

BK1545 with platform 480x450mm

