

SPECIFICATION 1.5 - 3.0 Ton TAILIFT 4 wheel Electric Forklifts

Model			FB15	FB18	FB 20	FB 25	FB 30	FBT 15	FBT 18
System			AC	AC	AC	AC	AC	AC	AC
Capacity	Rated load	kg	1500	1750	2000	2500	3000	1500	1750
Load Center	Distance	mm	500	500	500	500	500	500	500
Power Type	Electric (Battery)		Electric	Electric	Electric	Electric	Electric	Electric	Electric
Dimensions	Lift height	mm	3000	3000	3000	3000	3000	3000	3000
	Overall length without forks	mm	2095	2095	2330	2330	2450	1940	1960
	Overall Width	mm	1115	1115	1200	1200	1260	1078	1078
	Min. height with closed mast	mm	1985	1985	1985	1985	1985	1985	1985
	Min. height with raised mast	mm	4220	4220	4220	4220	4220	4220	4220
	Height of head guard	mm	2040	2040	2150	2150	2150	2070	2070
	Height of the seat	mm	1030	1030	1150	1150	1150	1015	1015
Wheels	Number: Front/Rear		2X/2	2X/2	2X/2	2X/2	2X/2	2X/2	2X/2
	Size : Front		21x8x9-14PR	21x8x9-14PR	23x9-10	23x9-10	23x9-10	18x7-8	18x7-8
	Size : Rear		5.0-8-8P.R.	5.0-8-8P.R.	18x7-8	18x7-8	18x7-8	15x4 1/2-8	15x4 1/2-8
Battery	Battery voltage	v	48	48	48	48	80	48	48
	Min. capacity	AH/5HR	460	460	700	700	560	505	505
	Max. capacity		600	600	750	750	600	600	600
	Battery box size	mm	L975xW465xH760	L975xW465xH760	L1028xW530xH790	L1028xW530xH790	L1126xW610xH800	L1000xW525xH620	L1000xW525xH620
Motors	Pump motor	kw	15	15	15	15	22	15	15
	Drive motor	kw	8	8	8	8	9	6.5x2	6.5x2