



● Standard ● Option

Equipment	ITEM	TD25
Engine	Cyclone air cleaner	●
	Fire extinguisher	●
Brake & steering	Service brake (rear wheels)	●
	Parking brake lever	●
	Non-slip brake pedal	●
	Spring steel plate	●
	Semi hydraulic semi mechanic steering system	●
	Additional torque converter oil cooler*	●
Transmission	Automatic transmission	●
	Operator's standard seat	●
Seat	Operator's suspension seat	●
	Co-operator's standard seat	●
	Mechanical coupler	●
Coupler	Engine hood gas filled cylinder	●
	Windshield with roof	●
	Rearview mirrors	●
Body	Fuel meter	●
	Radiator temperature meter	●
Meters	Headlight · Turn Signal Light · Taillight · Hazard light · back up buzzer	●
	Glove compartment	●
Light & Switches	Electric fan	●
	Plate & labels	●

Model	Unit	TD20	TD 25		
Overall Size	Length	mm	3085	3085	
	Width	mm	1500	1500	
	Height	mm	1450	1450	
Vehicle Weight		kg	4000	4000	
Front axle loading / Rear axle loading		kg	1100 / 3000	1100 / 3000	
Draw bar pull (Max)		kg	2000	2500	
Wheelbase		mm	1650	1650	
Tires	Front		6.50-10	6.50-10	
	Rear		7.00-15	28'9-15	
Gradeability			23°	23°	
Ground clearance		mm	210	210	
Turning Radius		mm	3250	3250	
Speed (Max)		km/h	25-30	25-30	
Braking Length		m	6	6	
Engine	Type		YANMAR 4TEN98	PERKINS 1104D	
	Cylinder number		4	4	
	Bore x Stroke	mm x mm	92 x 100	98 x 110	
	Displacement	L	2.659	3.319	
	Ratio		21.3	21.3	
	Rated Power	KW	34.7	46	
	Rated Speed	r/min	2450	2300	
	Fuel		Diesel fuel	Diesel fuel	
	Low idel	r/min	850±50	850±50	
	Rotation direction		Counterclockwise Viewed From Flywheel Side	Counterclockwise Viewed From Flywheel Side	
	Overall dimension	mm	710 x 516 x 758	710 x 516 x 758	
	Transmission	Type		OKAMURA(Auto shift)	OKAMURA(Auto shift)
		Forward I		3.07	3.07
Forward II			2.13	2.13	
Reverse			2.4	2.4	